

1

2

3

4

5

6

7

8

A

B

C

D

E

A

B

C

D

E

颜色要求:

A-class: 100,0,100,0;



B-class: 70,0,100,0;



C-class: 30,0,100,0;



D-class: 0,0,100,0;



E-class: 0,30,100,0;



F-class: 0,70,100,0;



G-class: 0,100,100,0;



192mm

96mm



BERKLAYS

BSSICE556S4EX



318 kWh/annum



184 L



372 L



39dB

ABCD

2019/2016

技术要求

- 1、油墨颜色按照图纸印刷（彩色的注明色值），印刷应清晰，不能有印刷缺陷；
- 2、切边应成平直/圆滑，不能歪斜；贴纸应平整，牢固，边角不能起翘或不粘；
- 3、材料应符合RoHS要求；
- 4、公差±2mm，其他未注公差尺寸；公差按照GB/T1804-M执行；
- 5、封样合格后方可批量供货。

标记	处数	分区	更改文件号	更改内容描述	签名	更改日期	实施日期
设计	张宇婷		2024.05.21	名称			版本号 V00
核对	李霞		2024.05.21	BERKLAYS留尼旺BSSICE556S4EX (BCD-606WH1)能效			状态
批准	唐应敏		2024.05.21	材料			比例 1:1 图幅 A3
合肥雪祺电气股份有限公司				不干胶/可移胶(覆膜)	编码 YZ000172506		
重量		数量		共 张		第 张	

1

2

3

4

5

6

7

8